



FACSIMILE TRANSMISSION SHEET

July 11, 2003

PLEASE DELIVER THE FOLLOWING PAGES TO:

NAME: Dang D Le, Examiner COMPANY: U.S. Patent and Trademark Office, Art
Unit 2834
FAX NUMBER: 703-872-9318 TELEPHONE: 703-305-0156

FILE NUMBER: 002209.879 TOTAL PAGES (INCLUDING COVER): 6
FROM: Gwendolyn L. Gill, Associate DIRECT DIAL: 704.331.7569

COMMENTS OR SPECIAL INSTRUCTIONS

IF YOU DO NOT RECEIVE THE TOTAL NUMBER OF PAGES INDICATED ON THIS TRANSMISSION SHEET, PLEASE CALL US AT 704.350.4428.

In re U.S. Patent Application of:

N. Coenen)	Docket: 2209.879 (WSC-2130)
Serial No.: 09/898,938)	Confirmation No. 1947
Filed: July 3, 2001)	
For: ROTOR SPINNING DEVICE WITH A)	Examiner: Le, Dang D
CONTACTLESS, PASSIVE, RADIAL)	
BEARING FOR THE SPINNING ROTOR)	Art Unit: 2834

FAX RECEIVED

JUL 11 2003

TECHNOLOGY CENTER 2800

RESPONSE AND REQUEST FOR RECONSIDERATIONCERTIFICATE OF TRANSMISSION UNDER 37 CFR § 1.8

I hereby certify that this correspondence is being facsimile transmitted to the United States Patent and Trademark Office at 703-872-9318, on the date indicated below.

7/11/2003
DATEGwendolyn L. Gill
GWENDOLYN L. GILL

THIS COMMUNICATION MAY CONTAIN CONFIDENTIAL OR LEGALLY PRIVILEGED INFORMATION AND IS INTENDED ONLY FOR THE USE OF THE INDIVIDUAL OR ENTITY NAMED ABOVE. IF YOU ARE NOT THE INTENDED RECIPIENT, YOU ARE HEREBY NOTIFIED THAT ANY DISSEMINATION, DISTRIBUTION, COPYING OR OTHER USE OF THIS COMMUNICATION OR ANY INFORMATION CONTAINED HEREIN IS STRICTLY PROHIBITED. IF YOU HAVE RECEIVED THIS COMMUNICATION IN ERROR, PLEASE NOTIFY US IMMEDIATELY BY TELEPHONE COLLECT AND RETURN THE ORIGINAL MESSAGE TO US AT THE ADDRESS BELOW VIA THE U.S. POSTAL SERVICE. WE WILL BE GLAD TO REIMBURSE YOU FOR POSTAGE. THANK YOU.

KENNEDY COVINGTON LOBDELL & HICKMAN, L.L.P.
CHARLOTTE RALEIGH RESEARCH TRIANGLE PARK ROCK HILL

www.kennedycovington.com
telephone 704.331.7400
facsimile 704.331.7598

HEARST TOWER, 47th FLOOR
214 NORTH TRYON STREET
CHARLOTTE, NORTH CAROLINA 28202

IN THE UNITED STATES PATENT AND TRADEMARK OFFICE

In re U.S. Patent Application of:

N. Coenen)	Docket: 2209.879 (WSC-2130)
Serial No.: 09/898,938)	Confirmation No. 1947
Filed: July 3, 2001)	
For: ROTOR SPINNING DEVICE WITH A)	Examiner: Le, Dang D
CONTACTLESS, PASSIVE, RADIAL)	
BEARING FOR THE SPINNING ROTOR)	Art Unit: 2834

Charlotte, North Carolina

Mail Stop Non-Fee Amendment
Commissioner for Patents
P.O. Box 1450
Alexandria, VA 22313-1450

RESPONSE AND REQUEST FOR RECONSIDERATION


Sir:

In response to the Office Action dated May 21, 2003, reconsideration and withdrawal of the rejections is requested pursuant to the remarks provided below. The claims, as shown, have not been amended in this response.

FAX RECEIVED

JUL 11 2003

TECHNOLOGY CENTER 2800

CERTIFICATE OF TRANSMISSION UNDER 37 CFR § 1.8	
I hereby certify that this correspondence is being facsimile transmitted to the United States Patent and Trademark Office at 703-872-9318, on the date indicated below.	
7/11/2003 DATE	 GWENDOLYN L. GILL

0251560.01
LIB: C2

1. (Previously amended) A rotor spinning device comprising a contactless, passive, radial bearing for the spinning rotor and a damping device external the passive radial bearing for damping radially directed oscillations of the spinning rotor, the damping device comprising a sensor arrangement, a control arrangement and an operating arrangement, the operating arrangement having at least two stationary magnetic operating elements arranged to act directly at least at one active site on a permanent magnet fixedly connected with the rotor shaft for rotation therewith, the rotating permanent magnet comprising an operative element of the passive bearing of the spinning rotor.

2. (original) The rotor spinning device in accordance with claim 1, characterized in that the sensor device at the active site comprises at least two sensor elements for detecting radial position deviations of the rotor shaft, and the sensor elements and the operating elements at the active site are arranged in a plane extending vertically in respect to the axis of rotation.

3. (original) The rotor spinning device in accordance with claim 1, characterized in that the operating elements are arranged with an angular offset in respect to the sensor elements of the active site.

4. (original) The rotor spinning device in accordance with claim 2, characterized in that the two operating elements are arranged angularly offset by 90 degrees in respect to each other, and the two sensor elements are arranged angularly offset by 90 degrees in respect to each other.

5. (original) The rotor spinning device in accordance with claim 1, characterized in that an additional operating element is assigned to each operating element and is located diametrically opposite in respect to the axis of rotation, and that each operating element and the additional operating element act in the same direction and with an essentially equal force on the rotating magnetic element.

6. (original) The rotor spinning device in accordance with claim 1, characterized in that the rotating magnetic element comprises a permanent magnet ring enclosing the rotor shaft, and the operating elements are arranged at an axial distance in front of the permanent magnet ring.

0251560.01
LJB: C2

7. (original) The rotor spinning device in accordance with claim 1, characterized in that the control device comprises elements for an exclusively capacitive coupling of the signals generated by the sensor elements.